

WPS 48



Highly Accurate Sensors Can Also Be Adaptive

Key Features

- **Zero recalibration** – sensor adapts automatically to any material (clear, opaque, metallic, nonwoven, mesh)
- **Compact form factor** – 48 mm (1.9 in) sensing range in a small housing
- **Material-agnostic detection** – fiber-optic technology based on light scattering and spatial filtering
- **Temperature immune** – unlike ultrasonic sensors, performance unaffected by temperature changes
- **One sensor, multiple applications** – edge guiding, width measurement, centerline detection

Benefits

- **Stop losing hours** to sensor recalibration when switching between materials
- **Eliminate changeover delays** – no manual sensor adjustments between product runs
- **End quality escapes** caused by undetected sensor drift between changeovers
- **Remove safety risks** from operators accessing sensors in awkward positions
- **Prevent hidden scrap** from temperature-related inaccuracies that plague ultrasonic sensors

*Note: WPS is a legacy product line. For new installations, consider the **ODC 48** with enhanced features.*

Specifications

Sensor Type	Fiber Optic (diffuse-reflective)	Sensing Range	48 mm (1.9 in)
Image Sensor	1D image sensor	Resolution	0.0635 mm (0.0025 in)
Repeatability	>99.9%	Working Distance	15-25 mm (0.6-1.0 in)
Response Time	20 ms standard	Operating Temp	-10°C to 65°C (14°F to 150°F)
Protection Class	IP54	Controller Required	Yes (SCU5 only)
Status	Legacy Product – Consider ODC 48 for new installations		

Applications

- Edge position sensing on narrow web applications
- Web guiding for converting lines
- Width measurement for narrow materials
- Centerline detection

Compatibility

SUPPORTED LINE SPEEDS

1000+ fpm

SUPPORTED MATERIAL TYPES

Porous/Perforated, Nonwoven

SUPPORTED WEB WIDTHS

Wide (48"-72"), Narrow (<12")

Available Configurations

Part Number	Configuration
3-400012	WPS 48-IR QD (1" Mounting)
3-400022	WPS 48-WL QD (1" Mounting)
3-400032	WPS 48-UV QD (1" Mounting)
3-401012	WPS 48-IR QD (NW Rail)

Part Number	Configuration
3-401022	WPS 48-WL QD (NW Rail)
3-402012	WPS 48-IR QD (No Mounting Bracket)
7-020001	1" Mounting Bracket for WPS and ODC Sensors
7-020004	1.5" Mounting Bracket for WPS and ODC Sensors
7-020005	Mounting Bracket for 1" or 25 mm Extrusion for WPS, ODC and 1DC Sensors
7-020006	Mounting Bracket for 1.5" or 40 mm Extrusion for WPS, ODC and 1DC Sensors

Supporting Documentation

Manuals (3)

- ARIS Web Position Sensor Product Manual
- Sensor Installation Recommendations
- Sensor Installation Recommendations: Inspection Applications

2D Drawings (4)

- New Mounting Brackets for WPS, ODC and 1DC sensors - 1.5 in or 40 mm extrusion
- New Mounting Brackets for WPS, ODC and 1DC sensors - 1in or 25 mm extrusion
- WPS 48-xx QD: 2D Drawing (pdf)
- WPS 48: 2D Drawing (DXF)

3D Models (7)

- 1.5in Mounting Bracket for WPS and ODC Sensors
- 1in Mounting Bracket for WPS and ODC Sensors
- Mounting Bracket for 1.5in or 40mm Extrusion for WPS, ODC and 1DC Sensors
- Mounting Bracket for 1in or 25mm Extrusion for WPS, ODC and 1DC Sensors
- WPS 48-xx QD (1" Mounting)
- WPS 48-xx QD (No Mounting Bracket)
- WPS 48-xx QD (NW Rail)

Wiring Diagrams (4)

- SCU5 C(x)D Wiring with WPS Sensor (Industrial Ethernet)
- SCU5 D Wiring with WPS Sensor (Analog Output)
- SCU5 DD Wiring with WPS Sensor (Digital Output)
- SCU5 DI Wiring with WPS Sensor (Digital Input and Output)



Scan for datasheets, 3D models & full documentation

<https://r2r.tech/products/sensors/wps-48>

Ready to Get Started?

Contact our experts to discuss how this product fits your application.

Phone: +1 (888) 290-3215 | **Email:** experts@r2r.tech | **Web:** r2r.tech